



C10LNC Series
WR10 Low Noise Converters
75 to 110 GHz

DESCRIPTION

The C10LNC Series is a low noise converter developed for full waveguide band up and down conversion applications in WR10 (75-110 GHz). The design leverages our fundamental mixer technology to satisfy the needs for optimized performance criteria. Our converters involve optimizing performance for size, output power, conversion loss, stability, group delay, noise figure, and bandwidth. Contact OML to discuss your specific requirements.



HIGHLIGHTS

- Full waveguide band coverage
- Low conversion loss performance

APPLICATIONS

- Versatility to satisfy multiple applications
- Noise figure measurements

ELECTRICAL AND PERFORMANCE SPECIFICATIONS (+25°C)

After a one hour warm-up period, the C10LNC satisfies the following specifications.

Electrical Characteristics¹	TYPICAL
RF Input Frequency Range (GHz)	75.0 to 110.0
LO Input Frequency Range (GHz)	12.5 to 18.3
IF Output Frequency Range (MHz)	10 to 300
RF Input Compression (P_{1dB}) (typ.)	TBD
Conversion Loss (typ.)	17 dB
LO Input Power	+7 to +10 dBm
VSWR (typ.)	
RF Input	1.5:1
LO Input	1.6:1
IF Output ²	2.0:1
Interface	
RF Input	WR-10 ³
LO Input	SMA(f)
IF Output	SMA(f)
DC Input	7 Pin Circular Bayonet Plug
DC (+12 VDC) Power Requirements	1.5 A, typ.
Operating Temperature Range (°C)	20° - 30°

¹) Specifications subject to change without notice

²) With IF amplifier

³) Test Port Flange Configuration is compatible with MIL-DTL-3922/54 and MIL-DTL-3922/67D

SIMPLIFIED BLOCK DIAGRAM

