



Waveguide Flange Designation

Band	EIA Designator	IEEE 1785.1	MIL-DTL-3922/67E	MIL-F-3922/67B	UG	Flange Type
Ka	WR-28	WM-7112	-005	-005	UG-599/U	Square, four thru holes
Q	WR-22	WM-5960	-006	-006	UG-383/U	Circular, four #4-40 holes/ two dowel pin holes
U	WR-19	WM-4775	-007	-007	UG-383/U-M	Circular, four #4-40 holes/ two dowel pin holes
V	WR-15	WM-3759	-008	-008	UG-385/U	Circular, four #4-40 holes/ two dowel pin holes
E	WR-12	WM-2539	-009	-009	UG-387/U	Circular, four #4-40 holes/ two dowel pin holes
W	WR-10	WM-2540	-010	-010	UG-387/U-M	Circular, four #4-40 holes/ two dowel pin holes
F	WR-08	WM-2032	-010-M	-010-M	UG-387/U-M	Circular, four #4-40 holes/ two dowel pin holes
D	WR-06	WM-1651	-010-M	-010-M	UG-387/U-M	Circular, four #4-40 holes/ two dowel pin holes
G	WR-05	WM-1295	-010-M	-010-M	UG-387/U-M	Circular, four #4-40 holes/ two dowel pin holes
Y	WR-04	WM-1094	-010-M	-010-M	UG-387/U-M	Circular, four #4-40 holes/ two dowel pin holes
J	WR-03	WM-864	-010-M	-010-M	UG-387/U-M	Circular, four #4-40 holes/ two dowel pin holes
--	WR-02.2	WM-570	-010-M	-010-M	UG-387/U-M	Circular, four #4-40 holes/ two dowel pin holes
--	WR-01	WM-250	-010-M	-010-M	UG-387/U-M	Circular, four #4-40 holes/ two dowel pin holes